

# EC-TYPE EXAMINATION CERTIFICATE (MODULE B)

Certificate No: MEDB00001WT Revision No: 1

Application of: Directive 2014/90/EU of 23 July 2014 on marine equipment (MED), issued as "Forskrift om Skipsutstyr" by the Norwegian Maritime Authority. This Certificate is issued by DNV AS under the authority of the Government of Norway.

This is to certify: That the A & B Class divisions fire integrity: A class divisions.

with type designation(s) A-60 Aluminium Bulkhead - 50 mm FireMaster Marine Plus Blanket

# Issued to Thermal Ceramics UK Ltd

Wirral, Merseyside, United Kingdom

is found to comply with the requirements in the following Regulations/Standards: Regulation (EU) 2020/1170, item No. MED/3.11a. SOLAS 74 as amended, Regulation II-2/3.2 & II-2/9, IMO 2010 FTP Code, IMO MSC/Circ.1120 and IMO MSC.1/Circ.1434, IMO MSC.1/Circ.1435.

Further details of the equipment and conditions for certification are given overleaf.

This Certificate is valid until 2026-05-10.

Issued at Høvik on 2021-05-11

DNV local station: Manchester

Approval Engineer: Helge Bjørnarå



Notified Body No.: 0575

for DNV AS

Sverre Olav Bergli Head of Notified Body

A U.S. Coast Guard approval number will be assigned to the equipment when the production module has been completed and will appear on the production module certificate (module D, E or F), as allowed by the "Agreement between the United States of America and the EEA EFTA states on the mutual recognition of Certificates of Conformity for Marine Equipment" signed 17 October 2005, and amended by Decision No 1/2019 dated February 22nd, 2019.



The mark of conformity may only be affixed to the above type approved equipment and a Manufacturer's Declaration of Conformity issued when the production-surveillance module (D, E or F) of Annex B of the MED is fully complied with and controlled by a written inspection agreement with a Notified Body. The product liability rests with the manufacturer or his representative in accordance with Directive 2014/90/EU. This certificate is valid for equipment, which is conform to the approved type. The manufacturer shall inform DNV AS of any changes to the approved

equipment. This certificate remains valid unless suspended, withdrawn, recalled or cancelled.

Should the specified regulations or standards be amended during the validity of this certificate, the product is to be re-approved before being placed on board a vessel to which the amended regulations or standards apply.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.





Job Id: Certificate No: Revision No:

344.1-000502-114 MEDB00001WT

## **Product description**

A-60 Aluminium Bulkhead - 50 mm FireMaster Marine Plus Blanket,

composed of a structural aluminium bulkhead insulated with a single layer of 50 mm thick FireMaster Marine Plus Blanket (manufactured by Thermal Ceramics with density 70 kg/m<sup>3</sup>) applied across the top of stiffeners following their contours.

The nominal blanket width is 610 mm and is to be compressed to a width of 580 mm to ensure compression at joints.

The blankets are held in place using stainless steel pins with bi-metallic anchor ( $\emptyset$  3 mm / typically 65 mm long) welded to the bulkhead and 38 mm friction-fit stainless steel washers. The pins are to be installed with a nominal spacing of 240 mm, whereas pins at the joints between blankets shall have a nominal spacing of 100 mm from the blanket edge.

The installation is to be performed according to the manufacturers Fire Protection Systems Information, reference No. FM MS 02 PW and No. FM 4.63.

## **Application/Limitation**

Approved for use as a vertical fire retarding division of class A-60.

Restricted application: Fire hazard from the insulated side only

The bulkhead may also be used in vertical fire resisting divisions in High Speed Craft.

The insulation material FireMaster Marine Plus Blanket has to be approved according to the Marine Equipment Directive and bear the Mark of Conformity.

Each product is to be supplied with its manual for installation and maintenance.

#### Type Examination documentation

Test report No. 2006CS012383 dated 21 July 2006 from RINA, Genoa, Italy.

Thermal Ceramics Fire Protection Systems Information, reference No. FM MS 02 PW and No. FM 4.63, Rev. 1.

#### **Tests carried out**

Tested according to IMO FTPC Part 3 (IMO Res. A.754(18)) and in compliance with IMO 2010 FTP Code Ch. 8.

#### Marking of product

The product is to be marked with name and address of manufacturer, type designation, fire technical rating, the MED Mark of Conformity and USCG approval number if applicable (see page 1).