



Superwool[®] Plus Textiles

Product Data Sheet

Product Description

Superwool Plus textiles are produced using the low bio persistence Superwool Plus fibre which is manufactured from pure raw materials with a classification temperature of 1200°C (2190°F).

The use of the patented low-shot fiberisation technology, ultra-pure raw materials offers excellent thermal and physical features to our Superwool Plus Textile portfolio.

The Textile portfolio includes the following and they may be reinforced by E-Glass fibre or Stainless Steel Wire:

- Superwool Plus Tapes are created by weaving a number of plied Superwool Plus yarns, reinforced with E-Glass or Stainless Steel Wire.
- Superwool Plus Ropes are created with strips of Superwool Plus Blanket that are over-braided with an E-glass yarn, a Stainless Steel yarn, or Superwool yarn with E-Glass or Stainless Steel reinforcement.
- Superwool Plus Twisted Rope is twisted threads made of Superwool Plus fibre yarn reinforced with E-glass or stainless steel.
- Superwool Plus Braided Rope is a braided Superwool Plus fibre yarn reinforced with E-glass or stainless steel around a core of yarns made of Superwool Plus reinforced with E-glass yarn. Available in round or square cross section.
- Superwool Plus Braided Sleeving is a woven form of Superwool Plus fibre yarn reinforced with E-glass or stainless steel.
- Superwool Plus Cloth is a woven mesh of Superwool Plus fibre yarn reinforced with E-glass or stainless steel.

Applications

- **Yarn:** Used for weaving or braiding into different kinds of textiles;
- **Fibre tape:** For industrial thermal insulation, piping and electrical cable lining, shielding against heat radiation, oven door curtain, flange joint etc.
- **Fibre rope:** Based on the different requirements, can be produced into twisted rope, 3-ply twisted rope and roving twisted rope. Used for high temperature pipe insulation and sealing, electrical cable lining, thermal insulation for coke oven and cracking furnace, door sealing for electric furnace and drying oven, sealing for boiler and high temperature gas etc.
- **Braided rope:** Used for thermal insulation and sealing in various areas including ovens, boilers, burners, heat exchangers, furnace cars, chimneys, valves and pumps etc.
- **Fibre cloth:** Used for large area industrial thermal insulation, fire protection and base cloth of fire curtain, welding curtain and coating cloth etc.
- **Sintered cloth or tape:** Cloth or tape after the specific heat treatment can effectively avoid generating fires and smokes during the service.

Environmental & Health Safety

Superwool low biopersistent fibres manufactured by Morgan Advanced Materials are not classified as carcinogenic by IARC or under any national regulations on a global basis. They have no requirements for warning labels under GHS (Globally Harmonised System for the classification and labelling of chemicals).

In Europe, Superwool fibres meet the requirements specified under Note Q of European Regulation EC/1272/2008 (on Classification, Labelling and Packaging of substances and mixtures). All Morgan Advanced Materials Superwool low bio persistent fibre products are therefore exonerated from classification and labelling as hazardous in Europe.

Superwool[®] Plus Textiles

Product Data Sheet



Main Properties		Superwool Plus Textiles
Region of Manufacture		Asia
Fibre Classification Temperature, °C (°F)		1200 (2190)
E-Glass Reinforced Continuous Working Temperature, °C (°F)		400 (752)
Steel Reinforced Continuous Working Temperature, °C (°F)		800 (1472)
Loss on ignition,%		<20
Chemical Composition, %		
	SiO ₂	62 - 68
	CaO	26 - 32
	MgO	3 - 7
	Other	<1

Product Availability

Superwool Plus Textiles are manufactured currently in our Asia region. Textiles are available globally, but request you contact your regional Morgan Advanced Materials - Thermal Ceramics representative to provide specific packaging availability for your local business needs.

Standard Dimensions and Availability		
Yarn, tex	Tex: 420x2, 525x2, 625x2, 630x2, 830x2, 1000x2, 830x3, 2000x1, 2000x2, 2250x2	
Fibre Cloth, mm	Thickness: 2,3,5	Width: 1000 - 1500
Fibre Tape, mm	Thickness: 2,3,5	Width: 15, 25, 50, 75, 100, 120, 150, 200, 250, 500
Fibre Rope, mm	Diameter : 3, 4, 5, 6, 8, 10, 12, 13, 14, 16, 18, 20, 25, 30, 35, 40, 50, 60, 75, 100, 120	
Braided Rope, mm	Diameter / Length: 6, 8, 10, 12, 14, 16, 18, 20, 25, 30, 35, 40, 50, 60, 75, 100, 120	

The product(s) represented are intended for industrial refractory applications. The values and application information in this datasheet are given for guidance only. The values and the information given are subject to normal manufacturing variation and may be subject to change without notice. Morgan Advanced Materials – Thermal Ceramics makes no guarantees and gives no warranties about the suitability of a product, and you should seek advice to confirm the product's suitability for use with Morgan Advanced Materials.