

Reference	FM 4.103 Rev 1
Release Date	October 2013



Fire Protection Systems Information

A15 Steel Bulkhead

Fire towards EITHER side

Profile Wrap System

Accompanies Method Statement FM-MS 01 PW

Product	FireMaster Marine Plus Blanket
Application Requirements	25mm x 64 kg/m ³ FireMaster Marine Plus Blanket applied in one single layer onto stiffened side of bulkhead.
Anchoring	CD welded steel pins 3mm diameter 12 to 25mm longer than blanket thickness. Friction fit retaining washers.
Weight	1.6 kg/m ² on flat area and over stiffeners.
System Drawing Reference	FM CAD12-4.103
System Features	No chicken mesh required Flexible anchor pin spacing and joint locations. Joints between blanket can be any location (refer to drawing)
Certification	DNV EU MED US Coastguard Transport Canada

Reference	FM 4.103 Rev 1
Date of Issue	October 2013

Drawing FM CAD 12 4.103 A15 Steel Bulkhead Fire Either Side

25mm x 64 kg/m³ applied in one single layer on stiffened side of bulkhead plate. Stiffeners to be packed with blanket. Note: Blanket joint locations shown on this drawing are typical examples of where joints may occur in the lining. Joints may be placed anywhere and not exactly as shown in the drawing below.

